



DINO Solar Light Tower

KEY FEATURES

Mobile solar trailer units utilise 2 units solar panel and 18ft vertical mast with one man job trailer to keep rapid deployment system, no fuel cost and no noise.

APPLICATIONS

This solar trailer is ideal for a wide range of applications including construction, industrial, civil works, rental, monitoring, and government projects.

ORDERING INFORMATION

STLTWR03S

CATALOG		COMMENTS
PROJECT		
PREPARED BY		
DATE		



CCTV Camera
Option Available

SOLAR SPECIFICATIONS

Solar Panel	2*380W Monocrystal Silicon Solar Panel
Battery	Gel Battery
Capacity	4*150AH DC 12V
System Voltage	DC 24V
Charge Time	10 Hours
Charge Temp	-25°C/-13°F to 60°C

LIGHT MAST SPECIFICATIONS

Mast Head Length	26 inches
Materials	Galvanized Steel
Type of Mast	Round Type, Telescopic
Height	18-23ft 5 Sections

TRAILER SPECIFICATIONS

Tow Hitch	1.96 Ball / 2.76 Ring
Tire & Rim	185R14C
Axle	Single Axle.
Dimensions	118.5 inches X 77.4 inches X 104.7 inches
Weight	1565 Lb



DINO Solar Light Tower

CATALOG		COMMENTS
PROJECT		
PREPARED BY		
DATE		

LED LAMP SPECIFICATIONS

Lamp Qty	4
Lamp Type	LED
Voltage	DC 24V
Total Watts	240W
Single-lamp Watts	60W
Total Lumens	36,000 LMS
Single Lamp Lumens	9,000 LMS
LED Life Expectancy	80,000+Hours
Color Temp	5700±300K
Beam Angle	40° Narrow Flood / 60° Flood / 120° Wide Flood
Ambient Temp Range	-40°C/-40°F to 50°C
Materials	Aluminum Extrusion
Mount	U Bracket
Housing Color	Gray



1460 Park Avenue.
Emeryville, CA 94608 USA
soltechlighting.com

SOLTECH LLC reserves the right to update all product data sheets at any time. Consult SOLTECH marketing specialists for publication updates at hello@soltechlighting.com

Copyright©2022-2023 SOLTECH LLC, All Rights Reserved.